CORRECTED VERSION

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 2 June 2005 (02.06.2005)

PCT

(10) International Publication Number WO 2005/050102 A2

(51) International Patent Classification7:

F24J

(21) International Application Number:

PCT/IL2004/001061

(22) International Filing Date:

18 November 2004 (18.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 158968

20 November 2003 (20.11.2003) 11.


- (71) Applicant and
- (72) Inventor: DAGAN, OFER [IL/IL]; Sha'ar Ha'Amakim, 30097 (IL).
- (74) Agent: PINK, Yakov; 34 Ben Yehuda Street, City Tower 16th Floor, 94230 Jerusalem (IL).
- (81) Designated States (unless otherwise indicated, for every

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- without international search report and to be republished upon receipt of that report



wherein the entire system is full of water. The water circulation goes from the bottom of the tank trough a fine-tube absorber plate, which is located between a transparent cover exposed to the sun and an insulated plate. The heated water passes through a second absorber that heats them to a usage temperature and cause them flows into the tank's space. The second absorber is created between the exposed wall of the tank, by a grid of tunnels that are grooved in a thermally insulated layer that are attached to the inside walls of the tank. The second absorber is covered with transparent cover too. The water flow into the upper part of the tank and a thermo-siphon valve prevents the back flow. After a double heating, the water is stored inside the tank and ready for use. The system can also have an electrical heating option, a flexible turbolator in the fin-tube absorber to be shrunk in case of freezing and flexible means inside the tank for the same purpose.



WO 2005/050102 A2



(15) Information about Correction: see PCT Gazette No. 30/2005 of 28 July 2005, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.